


# Flush Pendent Sprinkler

The Flush Pendent Sprinkler is an automatic flush plate sprinkler designed for commercial occupancies. The sprinklers are decorative and low profile with the Node device hiding the deflector and gasket assemblies. The sprinklers are designed with a quick response time rating and proven water distribution characteristics.

The Flush Pendent Sprinkler has been designed to be visually consistent with the Node product range. Node provides the visual casing and Rapidrop provides the sprinkler head and connection.



## Product Features

- Easy to install
- Colour matched to channel profile
- Quick response time
- Proven water distribution characteristic
- Available in various finishes

## Specifications

	Diameter	Height	Protrusion
Trimless Mount	90mm/3.54 in.	38.5mm/1.52 in.	21mm/0.82 in.
Flush Channel	90mm/3.54 in.	40mm/1.57 in.	21mm/0.82 in.

### General

- Compatibility: Rapidrop RD102 (CE)
- Response: Quick Response
- Type: SLP (Spray, Flush, Pendent)
- Maximum Working Pressure: 12.1 bar (175psi)
- Discharge Coefficient: K = 80 (5.6)
- Temperature Rating: 72°C (162°F),
- Finishes: White, Black and RAL colours on request
- Link: Fusible link
- Weight: .11 kg [.24 lbs]

### Certification

- Approvals: LPCB
- E.C. Certificate of Conformity: 0832-CPD-S0063