


# Concealed Pendent Sprinkler

The Concealed Pendent Sprinkler is an automatic flush plate sprinkler designed for commercial occupancies. The sprinklers are decorative and low profile with the Node device and cover plate hiding the deflector and gasket assemblies. The sprinklers are designed with a standard response time rating and proven water distribution characteristics.

The Concealed Pendent Sprinkler has been designed to be visually consistent with the Node product range. Node provides the visual casing and Rapidrop provides the sprinkler head and connection.



## Product Features

- Easy to install
- Colour matched to channel profile
- Standard response time
- Proven water distribution characteristic
- Available in various finishes

## Specifications

	Diameter	Height	Protrusion
Trimless Mount	90mm/3.54 in.	38.5mm/1.52 in.	5mm/0.20 in.
Flush Channel	90mm/3.54 in.	40mm/1.57 in.	5mm/0.20 in.

### General

- Compatibility: Rapidrop RD107 (CE), RD105 (UL)
- Response: Standard Response
- Maximum Working Pressure: 12.1 bar (175psi)
- Discharge Coefficient:  $K = 80$  (5.6)
- Temperature Rating: Sprinkler - 72°C (162°F), Cover Plate - 60°C (140°F)
- Finishes: White, Black and RAL colours on request
- Link: Fusible link
- Weight: .11 kg [.24 lbs]

### Certification

- Approvals: LPCB
- E.C. Certificate of Conformity: 0832-CPD-2067
- UL Listed