


DALI Network Sensor

The Node DALI Network Sensor detects occupancy and ambient lighting as part of a DALI lighting control system.

The DALI Network Sensor has been designed to be visually consistent with the Node product range.



Product Features

- Detection of occupancy
- Easy to install
- Ambient light detection
- Available in various finishes

Specifications

| | Diameter | Height | Protrusion |
|------------------|---------------|-----------------|--------------|
| Surface Mount | 90mm/3.54 in. | 40mm/1.57 in. | 7mm/0.28 in. |
| Recessed Channel | 90mm/3.54 in. | 58mm/2.28 in. | 7mm/0.28 in. |
| Trimless Mount | 90mm/3.54 in. | 38.5mm/1.52 in. | 7mm/0.28 in. |
| Flush Channel | 90mm/3.54 in. | 40mm/1.57 in. | 7mm/0.28 in. |

General

- Operating Temperature: -10°C [14°F] to 35°C [95°F]
- Humidity: 5 to 95% Non-Condensing
- Type: Class 2
- IP Rating: IP40
- Weight: .11 kg [.24 lbs]

Input

- Voltage: 9.5V DC – 22.5V DC via DALI
- Current: 8mA

Connection Type

- 2-Wire Cable

Range

- Motion Sensor Coverage:
 - Walk Across: 9m [29 ft] x 9m [29ft] at 2.8m [9ft]
 - Walk Towards: 5m [16 ft] x 5m [16ft] at 2.8m [9ft]

Communication Protocol

- DALI

Certification

- EMC-2004/104/EC
- LVD-2006/95/EC